



## PATENT ABSTRACTS OF JAPAN

(11) Publication number: 11181429 A

(43) Date of publication of application: 06.07.99

(51) Int. Cl.

C09K 21/12  
B05D 5/10  
C08K 5/5399  
C08L101/00  
// C08J 5/00

(21) Application number: 10032770

(22) Date of filing: 16.02.98

(30) Priority: 14.02.97 JP 09 29961  
15.10.97 JP 09281679

(71) Applicant: OTSUKA CHEM CO LTD

(72) Inventor: NAKANAGA TAKEFUMI  
YABUHARA TADAO  
TADA YUJI  
NISHIOKA YOICHI

(54) FLAME-RETARDANT, FLAME-RETARDANT  
RESIN COMPOSITION AND FLAME-RETARDANT  
RESIN MOLDED PRODUCT


groups are contained in an amount of 50-99.9% based on the total phenyl groups in the compounds of formulas I and II.

(57) Abstract:


COPYRIGHT: (C)1999,JPO

PROBLEM TO BE SOLVED: To obtain a flame-retardant not containing a halogen, having a high melting point and a low volatility, not deteriorating the original characteristics, such as mechanical characteristics and moldability, of resins, and useful for electric parts, electronic parts or the like by including a specific crosslinked phenoxyphosphazene compound.


SOLUTION: This flame retardant comprises a crosslinked phosphazene compound obtained by crosslinking one or more kinds of phosphazene compounds selected from the group consisting of a cyclic phosphazene compound of formula I [(n) is 3-25; Ph is phenyl] and a linear phosphazene compound of formula II [X is N=P(OPh)<sub>3</sub> or N=P(O)OPh; Y is P(OPh)<sub>4</sub> or P(O)(OPh)<sub>2</sub>; (n) is 3-1,000] with one or more kinds of crosslinking groups selected from the group consisting of 0-, m- and p-phenylene groups, biphenylene group and a group of formula III [A is C(CH<sub>3</sub>)<sub>2</sub>, SO<sub>2</sub>, S or O]. Each of the crosslinking groups is placed between the two phenyl group-released oxygen atoms of the crosslinked phosphazene compound, and the crosslinked phenyl



I



II



III